



TECHNICAL SPECS

MAX WORK SIZE mm (in)	<p>Φ530 × H760 (Φ20.86 × H29.92) - Standard (PC5, PC15)</p> <p>Φ500 × H760 (Φ19.68 × H29.92) - (PC11)</p>
WORKING SURFACE mm (in)	300 x 300 (11.81 x 11.81)
LOADING CAPACITY kg (lb)	250 (550)
TOOL TAPER	<p>CAT #40/BT - Standard</p> <p>HSK-A63 - Option</p>
NUMBER OF TOOLS	<p>60 : BT40 - Standard</p> <p>71 : BT40 - Option</p> <p>120/150/180/210/240 : BT40 - Option</p> <p>120/160/200/240/280/320 : BT40 - Option</p> <p>360/400/440/480/520 : BT40 - Option</p>
NUMBER OF PALLETS	<p>2 - Standard</p> <p>5 : Floor Pallet System - Option, 11 : Floor Pallet System - Option</p> <p>15 : Tower Pallet System - Option</p>
SPINDLE SPEED RPM	<p>15,000 : BT40 - Standard</p> <p>20,000 : BT40 - Option</p> <p>30,000 : BT40 - Option</p>
TRAVEL (X/Y/Z) mm (in)	500/560/500 (19.68/22.04/19.68)
RAPID TRAVERSE (X/Y/Z) m/min (ipm)	60 (2,362.20)
NC SYSTEM	Matsuura G-Tech 31i
INDUSTRIES	Automotive and High Performance, Medical