



## TECHNICAL SPECS

<b>MAX WORK SIZE</b> mm (in)	Φ630 × H900 ( Φ24.80 × H35.43 )
<b>WORKING SURFACE</b> mm (in)	400 x 400 ( 15.74 x 15.74 )
<b>LOADING CAPACITY</b> kg (lb)	400 ( 880 )
<b>TOOL TAPER</b>	CAT #40/BT - Standard HSK-A63 - Option
<b>NUMBER OF TOOLS</b>	60 : BT40 - Standard 61 : BT40 - Option 164/204/244/294 : BT40 - Option 120/160/200/240/280/330 : BT40 - Option
<b>NUMBER OF PALLETS</b>	2 - Standard 6 : Floor Pallet System - Option 12 : Tower Pallet System - Option
<b>SPINDLE SPEED</b> RPM	15,000 : BT40 - Standard 20,000 : BT40 - Option
<b>TRAVEL (X/Y/Z)</b> mm (in)	560/640/640 ( 22.04/25.19/25.19 )
<b>RAPID TRAVERSE (X/Y/Z)</b> m/min (ipm)	60 ( 2,362.20 )
<b>NC SYSTEM</b>	Matsuura G-Tech 31i
<b>INDUSTRIES</b>	Automotive and High Performance, Medical