



## TECHNICAL SPECS

<b>MAX WORK SIZE</b> mm (in)	Φ800 × H1,000 ( Φ31.49 × H39.37 )
<b>WORKING SURFACE</b> mm (in)	500 x 500 ( 19.68 x 19.68 )
<b>LOADING CAPACITY</b> kg (lb)	750 ( 1,650 )
<b>TOOL TAPER</b>	CAT #50/BT - Standard HSK-A100 Option
<b>NUMBER OF TOOLS</b>	60 : BT40 - Standard 61 : BT40 - Option 120/150/180/210/240 : BT40 - Option 164/204/244/294 : BT40 - Option 120/160/200/240/280/330 : BT40 - Option
<b>NUMBER OF PALLETS</b>	2 - Standard 6 : Floor Pallet System - Option
<b>SPINDLE SPEED</b> RPM	12,000 : BT40 - Standard 15,000 : BT40 - Option 20,000 : BT40 - Option
<b>TRAVEL (X/Y/Z)</b> mm (in)	1,050/920/990 ( 41.33/36.22/38.97 )
<b>RAPID TRAVERSE (X/Y/Z)</b> m/min (ipm)	60 ( 2,362.20 )
<b>NC SYSTEM</b>	Matsuura G-Tech 31i
<b>INDUSTRIES</b>	Automotive and High Performance